

250mm




M-D22
User Manual

Thank you!


Thank you for choosing relacart M-D22 dynamic microphone module. M-D22 is suitable for Relacart UR series handheld wireless transmitters, excellent off-axis directional, high sound pressure suitable frequency response curve restore various sounds accurately, whether it is speech or singing, can meet your needs and give you a true sound. The M-D22 dynamic microphone module is compatible with Shure® wireless microphone body.

M-D22 is a super cardioid directional dynamic microphone module, which can be flexibly matched with a variety of handheld transmitters, newly designed capsule, its supercardioid direction can make the microphone head better capture the sound, and accurately restore various sounds. The mesh cover of microphone is made of elastic steel wire, with a built-in wind shield, which can effectively filter out wind and explosion noise.

Frequency Response



Polar Pattern



Product specification

relacart UR series wireless
Connectivity: microphone body
Shure® wireless microphone body

Type: dynamic

Directivity: supercardioid

Frequency Response: 120-16000Hz

Flexibility: -53dB re 1V/Pa

Max SPL: 145dB@1%

Dimension: 53mmx79mm

Weight: 85g

Safety and maintenance



Please make sure that the equipment connected to your M-D22 complies with the safety regulations implemented in your country.

Support

If you have any inquiries or questions about your Relacart product, please contact us directly:
<http://www.relacart.com/contact>

This product complies with the standards listed in the declaration of conformity. Technical data are subject to change without notice.



70mm

250mm




Most Sincerely,
Your relacart Team
您最真诚的 relacart 团队

感谢!


感谢您选择relacart M-D22动圈话筒模组, M-D22适用于Relacart UR系列手持式无线发射器, 优异的离轴指向性, 高声压耐受和适合的频率响应曲线准确还原各种声音, 无论演讲或者演唱都能满足您的需求, 给您真实的声音还原。M-D22动圈话筒模组可兼容Shure® 无线麦克风主体。

M-D22 是一款超心型指向动圈话筒模组, 可以灵活匹配多种手持发射机, 全新设计的拾音头, 其超心型指向能更好捕捉话筒前面的声音, 并准确还原各种声音。话筒网罩使用弹性钢丝焊制而成, 内置防风海绵, 能有效过滤掉风声和气流噪音。

频率响应



极性响应



技术规格

连接: relacart UR系列无线麦克风主体
Shure® 无线麦克风主体

类型: 动圈

指向: 超心型

频率响应: 120-16000Hz

灵敏度: -53dB re 1V/Pa

最大声压级SPL: 145dB@1%

尺寸: 53mm x 79mm

重量: 85g

安全与维护



请确保您的M-D22所连接的设备符合贵国实施的安全规定。

支持

如果您的relacart产品出现任何问题或有任何疑问, 请直接与我们联系:
<http://www.relacart.cn/contact>

本产品符合《合格声明》所列标准。
技术资料如有更改, 恕不另行通知。



70mm

双面: 250 x 70 mm, 100克书写纸

红色框: 说明书尺寸

红色虚线: 折叠位置 (风琴折法)