

CS-302C | Chairman unit



Description

CS-302C is a high-quality conference system microphone that comes with a built-in high-definition OLED display screen, which allows users to easily view conference modes, speaking statuses, and various other information. The built-in speaker can directly output audio without the need for additional speaker connections. Additionally, the microphone has a headphone output port to meet users' requirements for audio privacy. The detachable microphone design enables users to easily remove and replace the microphone, ensuring device maintainability and reliability. To provide a better audio experience, the CS-302C adopts a metal windscreen to prevent unnecessary noise and wind interference. The braille touch design makes it easy for visually impaired users to operate, while also making the control panel more visually appealing and user-friendly.

Product Specification

Frequency Response:	50Hz-18KHz
Sensitivity:	-30dB+/-3dB(0dB=1V/Pa,f=1KHz)
Maximum input sound pressure level:	105dB(THD < 5%, f=1KHz)
Signal to noise ratio (A weighted):	> 100dBA (THD < 1%, f=1 KHz)
Distortion:	< 0.1%
Power Supply:	24V DC(supplied by the receiver)
Maximum Power of Speakers:	1.5W
Power Consumption:	0.8W-2.5W
Phone Connector:	3.5mm jack
Screen Type:	OLED
Unit Interface:	Anti drop 9P aviation plug
Weight:	950g
The length of microphone(mm):	340mm/420mm/480mm
The size of the microphone base:	182mmx 51mm x 110mm
Color:	Nickel black