

UR-260D | Dual-Channel Wireless Microphone



Description

UR-260D Series of condensed the technology essence that Relacart accumulated over a long period. With advanced technology, sophisticated design, stable performance, with beautiful appearance, convenient operation and attractive price, with superior professional quality to win the market competition. This series is suitable for the nightclub of high requirements, multi-functional hall, hotel, conference room and small to medium performance.

Product Specification

Main Frame Size:	EIA STANDARD 1U
Channels:	Dual Channel
Frequency Stability:	$\pm 0.005\%$ (0~50°C)
Carrier Frequency Range:	521.25MHz-936.85MHz
sampling rate:	96kHz 24-Bit
Default audio equalizer:	simulate of various cartridge sound
Modulation Mode:	FM stereo modulation
Operating Range:	80M typical (in open space)
Oscillation:	PLL synthesized
Sensitivity:	5dB μ V, S/N>60dB at 25 deviation
Max. Deviation Range:	± 45 KHz
S/N:	> 100dB
T.H.D.:	< 0.5% @ 1KHz
Frequency response:	45Hz-18KHz ± 1 dB
Power Supply:	DC 12~18V/1A
Weight:	2.0kg
Dimension (mm):	410mm(W)x43mm(H)x206mm(D)
Output Connector:	LR balanced & 6.3 ϕ phone jack unbalanced